



801 JUNIOR



603 JUNIOR



TORCH LIGHT



HOLSTER WITH
MAGNET



TEST LEAD
GRIPPER

TRMS, Auto Ranging, 6000 Counts LCD with Backlight, Torchlight, APO, Capacitance, Frequency, Duty Cycle, NCV (LED, Buzzer & EF Strength), Temperature & Holster with Magnet

Ranges

DC Voltage 60 / 600mV / 6 / 60 / 600 / 1000V

Accuracy $\pm (0.8\% \text{ rdg} + 5 \text{ dgt})$

AC Voltage 60 / 600mV / 6 / 60 / 600 / 750V

Accuracy $\pm (1.0\% \text{ rdg} + 10 \text{ dgt})$ on 60 / 600mV
 $\pm (1.0\% \text{ rdg} + 4 \text{ dgt})$ on all other ranges

AC Response 40Hz ~ 1KHz

DC Current 60 / 600mA / 6 / 10A

Accuracy $\pm (1.2\% \text{ rdg} + 4 \text{ dgt})$ on 60 / 600mA
 $\pm (3.0\% \text{ rdg} + 2 \text{ dgt})$ on 6A
 $\pm (5.0\% \text{ rdg} + 10 \text{ dgt})$ on 10A

AC Current 60 / 600mA / 6 / 10A

Accuracy $\pm (1.5\% \text{ rdg} + 3 \text{ dgt})$ on 60 / 600mA
 $\pm (3.0\% \text{ rdg} + 5 \text{ dgt})$ on 6A
 $\pm (5.0\% \text{ rdg} + 10 \text{ dgt})$ on 10A

AC Response 40Hz ~ 1KHz

Resistance 600Ω / 6 / 60 / 600KΩ / 6 / 60MΩ

Accuracy $\pm (0.8\% \text{ rdg} + 5 \text{ dgt})$

Capacitance 60.00 / 600.0nF / 6.000 / 60.00 / 600.0μF / 6.000 / 60.00 / 100.0mF

Accuracy $\pm (3.0\% \text{ rdg} + 5 \text{ dgt})$ on all ranges except
 $\pm (5.0\% \text{ rdg} + 20 \text{ dgt})$ on 60.00 nF
 $\pm (5.0\% \text{ rdg} + 5 \text{ dgt})$ on 60.00 / 100.0 mF

Frequency 60.00 / 600.0Hz / 6.000 / 60.00 / 600.0KHz / 6.000 / 10.00MHz

Sensitivity 200mV to 10V AC
 Accuracy $\pm (1.5\% \text{ rdg} + 5 \text{ dgt})$

Manual Ranging, 2000 Counts LCD with Backlight, Torchlight, APO, NCV (LED, Buzzer & EF Strength), HFE & Holster with Magnet

Ranges

DC Voltage 200mV / 2 / 20 / 200 / 1000V

Accuracy $\pm (0.5\% \text{ rdg} + 5 \text{ dgt})$

AC Voltage 200 / 750V

Accuracy $\pm (1.2\% \text{ rdg} + 10 \text{ dgt})$

AC Response 40Hz ~ 400Hz

DC Current 200mA / 10A

Accuracy $\pm (1.0\% \text{ rdg} + 5 \text{ dgt})$ on 200mA
 $\pm (3.0\% \text{ rdg} + 2 \text{ dgt})$ on 10A

AC Current 200mA / 10A

Accuracy $\pm (3.0\% \text{ rdg} + 2 \text{ dgt})$

AC Response 40Hz ~ 400Hz

Resistance 200Ω / 2 / 200KΩ / 2 / 20MΩ

Accuracy $\pm (1.0\% \text{ rdg} + 3 \text{ dgt})$

Duty Cycle 1% ~ 99%


Accuracy $\pm (1.5\% \text{ rdg} + 5 \text{ dgt})$

Temperature -20°C ~ 1000°C / -4°F ~ 1832°F

Accuracy $\pm (1.0\% \text{ rdg} + 3 \text{ dgt})$

Measuring Category CAT II 600V

SP Function Diode Test, Data Hold, Continuity Test / NCV Test (LED, Buzzer & EF Strength), Three 1.5V 'AAA' Battery

'

Battery Life 200 hours typical

Dimensions 147 x 71 x 45mm (approx.)

Weight 230gms Including Battery (approx.)

Accessories One Pair of Test Leads, Spare Fuse (0.6A/250V) x 2, Holster, Battery (installed), Instruction Manual & K Type Thermocouple (upto 260°C)

Measuring Category CAT II 600V

SP Function Diode Test, Data Hold, Continuity Test / NCV Test (LED, Buzzer & EF Strength)

Power Three 1.5V 'AAA' Battery

Low Battery ' 

Battery Life 200 hours typical

Dimensions 147 x 71 x 45mm (approx.)

Weight 230gms Including Battery (approx.)

Accessories One Pair of Test Leads, Spare Fuse (0.2A/250V) x 2, Holster, Battery (installed) & Instruction Manual

Accessories

K Type Bead Probe (upto 260 °C)

Model : TPK-B



K Type Stick Probe (upto 500°C)

Model : TP-02



Pair of Test Leads suitable for DMM/DTT

Model : TL-DMM/DTT



Pair of Test Leads suitable for Insulation Tester

Model : TL-IT

