

## 3 3/4 Digital Clamp Meter (Auto Range)

**MS 2002A**



**Features:**

- 3 3/4 Digits LCD with 42-segements bar graph, max. reading 3999
- SMT application
- Auto/ Manual range
- Data hold & LCD backlighting
- Low battery indication
- Audible continuity
- Over load protection

**Technical Specifications**

DCV	: 400/600V, ± 1.0%
ACV	: 400/600V, ± 1.5%
ACA	: 40/400A, ± 2.0%
OHM	: 400ohms, ± 1.0%
Clamp size	: 28mm (max.)
Dimension	: 194 x 72 x 35 mm
Weight	: 200gm Approx.
Battery	: 1.5V x 2, AAA size

## 3 /1/2 Digital Open Jaw Electrical Tester

**MS 2600**



**Features:**

- New open-jaw technology for AC current measurement, easy to operate
- Test leads can be inserted on back groove of the tester
- Versatility of use with capacitance, frequency and duty cycle measurement
- 3 3/4 Digits LCD display
- Auto/ Manual range
- Data hold & LCD backlit
- Auto power-off

**Technical Specifications**

DCV	: 4/40/400/1000V, ± 0.7%
ACV	: 4/40/400/750V, ± 0.8%
ACA	: 200A, ± 2.0% (50Hz~1000Hz)
OHM	: 400 /4K/40K/400K/4M/40M ± 1.2%
CAP	: 40n/400n/4 F/40 F, ± 4.0%
Frequency	: 10Hz~100KHz, ± 2.0%
Duty Cycle	: 0.1%~99.9%
Dimension	: 192 x 168 x 43 mm
Weight	: approx. 230gm
Battery	: 9V x 1, 6F22

## Vernier Calipers

**200-118**



(General 0~200x0.02mm)

**200-646**



(With Mechanical Meter  
0~150x0.02mm)

**200-647**



(With Mechanical Meter  
0~200x0.02mm)

**200-196**



(With Digital Meter  
0~150x0.01mm)

**200-197**



(With Digital Meter  
0~200x0.01mm)

## Digital Micrometer

**200-521**

(With Digital Meter 0~25x0.001mm)

