



961K

Anemometer

Specifications	Range	Resolution	Accuracy
m/s (meter per second)	0.80 ~ 30.00 m/s	0.01 m/s	±(2.0% + 50)
Km/h (kilometer per hour)	30.00 ~ 40.00 m/s	0.01 m/s	Reference
	2.88 ~ 108.0 km/h	0.01 km/h	±(2.0% + 50)
	108.0 ~ 144.0 km/h	0.1 km/h	Reference
ft/s (feet per second)	2.62 ~ 98.50 ft/s	0.01 ft/s	±(2.0% + 50)
	98.50 ~ 131.2 ft/s	0.01 ft/s	Reference
knots (nautical miles per hour)	1.6 ~ 58.30 knots	0.01 knots	±(2.0% + 50)
	58.30 ~ 77.70 knots	0.01 knots	Reference
mile/h (mile per hour)	1.80 ~ 67.20 mil/h	0.01 mil/h	±(2.0% + 50)
	67.20 ~ 90.00 mil/h	0.01 mil/h	Reference
ft/m (feet per minute)	157.5 ~ 5900 ft/m	1 ft/m	±(2.0% + 50)
	5900 ~ 7874 ft/m	1 ft/m	Reference
Auto Ranging	Yes		
Refresh Rate	3 Times / Second		
Min/Max/Avg	Yes		
Wind Scale	Level 0 ~ 12		
Unit	m/s, km/h, ft/s, knots, mile/h, ft/m, CMM, CFM, CMS		
Data Hold	Yes		
Backlight	Yes		
Auto Power Off	Yes		
Low Battery Indicator	Yes		
Power	1.5V AAA x 2 Batteries		
Operating Altitude	< 2000m		
Operating Temperature	-10°C ~ +50°C		
Storage Temperature	-20°C ~ +60°C		
Operating Humidity	< 80% RH		
Weight	100gms Including Battery (approx.)		
Dimension	176 x 40 x 27mm (approx.)		
Accessories	Carrying Case, Inst. Manual, 1.5V AAA x 2 Batteries (Installed)		



970K

Sound Meter

Specifications	Range	Resolution	Accuracy
dB	30dB ~ 130dB	0.1dB	±1.5dB (In the Reference Sound Pressure Level 94dB 1KHz)
Sampling Rate	Fast : 125ms, Slow : 1000ms		
Frequency Range	31.5Hz ~ 8KHz		
Noise	Aweighting		
Min /Max	Yes		
Unit	dB		
Data Hold	Yes		
Backlight	Yes		
Auto Power Off	Yes		
Low Battery Indicator	Yes		
Power	1.5V AAA x 2 Batteries		
Operating Altitude	< 2000m		
Operating Temperature	-10°C ~ +50°C		
Storage Temperature	-20°C ~ +60°C		
Operating Humidity	< 80% RH		
Weight	120gms Including Battery (approx.)		
Dimension	175 x 40 x 27mm (approx.)		
Accessories	Carrying Case, Inst. Manual, 1.5V AAA x 2 Batteries (Installed)		